



All Pictures shown are for illustration purpose only. Actual product may vary due to product enhancement.

# BSR KIT

With the same premium quality as always, preserving the old school tradition of manufacturing in cast iron, our BSR line of shop roasters got even better!

## Introducing the BSR KIT.

Equipped with VFD (Variable Frequency Drive) for drum speed and roaster's fan speed with potentiometers in the control panel and prepared for Cropster and Artisan software with a converter, a USB connection and 2 thermocouples with double readout, the roast masters now have total control over their roasting with the possibility to register the roasting profile and track with high precision the curves for a more consistent and better control batch by batch.

BSR KIT models are offered in 1, 3, 5, 15 and 25 kilos-batch capacity. <sup>(1)</sup>

Connect our roaster with **CROPSTER** or **ARTISAN** software for precise roasting profile to ensure the true consistency and repeatability batch by batch.



<sup>(1)</sup> BSR 1 KIT and BSR 3 KIT models don't have enough space to properly accommodate the variators, we must use the bigger structure of the BPR models – but it will still be a BSR!

Another advantage is that there is no need to place the roaster on a table because it will be sufficiently higher to be operated in a stand-up position.

- ▶ **JOPER** Roasters are made with **High-Quality CAST IRON** components and hand craft individual for best roast quality, control and consistency.
- ▶ Roasting drum with **double wall** and special mixing paddles to ensure optimal movement and mixing for excellent roasting results.
- ▶ 4 separate **Premium Efficiency motors**. All direct drive for quietness and low maintenance: Drum drive, cooling pan stir arms, roaster fan and cooler fan. (BSR 1 KIT does not have the cooling stir arms motor.)
- ▶ 2 thermocouples: Bean temperature and exhaust air temperature.



**SPECIALTY COFFEE ROASTERS**

KIT								
BSR 1	0.5 – 1 kg (4 kg/h)	12-15 min	3 min	400V/50Hz/3Ph 240V/60Hz/3Ph 208V/60Hz/3Ph	Propane Gas (LPG) or Natural Gas (LNG)	1465 x 855 x 1495 mm 57.6 x 33.6 x 58.8 in	170 kg	Cropster or Artisan software
BSR 3	1.5 – 3 kg (12 kg/h)					1750 x 1000 x 1660 mm 68.8 x 39.4 x 65.3 in	220 kg	
BSR 5	2.5 – 5 kg (20 kg/h)	2075 x 1160 x 2090 mm 81.6 x 45.6 x 82.2 in	450 kg					
BSR 15	7.5 – 15 kg (60 kg/h)	15-18 min	3-4 min			2440x1335x2305 mm 96 x 52.5 x 90.7 in	630 kg	
BSR 25	12.5 – 25 kg (100 kg/h)	4 min	2640x1560x2550 mm 103.9x61.4x100.3 in			850 kg		

(\*) Other voltages are available upon request.